

Limecoat Line

Limewax

Natural protective wax

Natural beeswax and limewater for protecting interior lime stuccoes. It makes the surface water-repellent without closing it to water vapour and, once burnished, gives it a soft touch and a satin appearance.

01 — PRODUCT

Type	Use	Application
Natural protective wax	Interior	Vertical surfaces · Ceilings
Finish	Tool	Colour
Satin · soft to the touch	Brush · mop or woollen cloth for burnishing	Translucent amber

02 — CHARACTERISTICS

Limewax is the final layer of the Limestucco Fine direct-water system, for showers and interior surfaces in contact with water. PRS Performance prevents the stucco from absorbing water, oils and grease; Limewax completes the closing of the pore and increases the resistance of the surface.

- Water-repellent
- Breathable
- Durable
- Naturally derived

03 — APPLICATIONS

	Interior	External	Compatible substrates Preparation of each substrate is detailed in the Limewax installation manual.
Wall	Suitable	Not suitable	
Ceiling	Suitable	Not suitable	
Wet area without direct water contact	Suitable	Not suitable	
Direct water contact	Suitable	Not suitable	

04 — TECHNICAL DATA

Type	Composition
Natural protective wax	Limewater, beeswax and natural additives
Thinning	Appearance
Undiluted	Thick liquid at 21 °C
Number of coats	Approximate consumption
Until the substrate is saturated, depending on its absorbency	0.2 L/m ² · per coat
Full drying time	Recoat time
24 h	30–60 min
Pack size	Application temperature
1 L · 4 L	5–30 °C

PERFORMANCE

Viscosity	385 ± 6.4 mPa·s	a 21 °C
pH	9	

05 — APPLICATION SYSTEM

01	02	03	04	05
Substrate dry, sound, well adhered and free from dust, stains or contaminants	Apply Limewax by brush in thin, even coats	Burnish with a clean mop or woollen cloth 30–60 min afterwards	Repeat until the substrate is saturated	Full drying 24 h

Substrate preparation, tools, times and execution criteria: Limestucco installation manual →

06 — CONDITIONS AND LIMITATIONS

Application temperature	5–30 °C
Storage	Original hermetically sealed container, in a cool, protected place. Clean off any residue with warm water so that the container closes properly.
Shelf life	Max. 24 months from manufacture
Limitations	Interior use. Do not apply where there is a risk of frost, wind or rain. It leaves a satin finish and the complete system may deepen the colour by between 10% and 20%. Surface protection does not replace the substrate's construction waterproofing.

07 — MATERIAL AND VARIATION

TO SPECIFY

Formma surface protection · Limecoat Line · Limewax · natural wax of beeswax and limewater, satin finish · applied by brush in thin, even coats until the substrate is saturated and burnished with a mop or woollen cloth 30–60 min after each coat · approximate consumption 0.2 L/m² per coat · applied between +5 °C and +30 °C.

08 — RELATED DOCUMENTATION

Limestucco Fine technical data sheet →

Limestucco Fine installation manual →

Applications and substrates matrix →

formmadesign.com/documentacion/limecoat

