

Limecoat Line



Limetech

Cleaning and maintenance · Seamless mineral system

Technical data sheet, colour chart and the product's remaining documentation:

formmadesign.com/documentacion/limecoat/limetech

Initial care	Wait two weeks after application before beginning to clean with cleaning products.
Use and protection	Avoid standing water and prolonged contact with moisture: do not leave wet rugs or towels on the floor. Keep the surface free of sand and grit, which can scratch it. Avoid knocks and scuffs from hard objects, and do not drag heavy objects or furniture: lift them and set them down carefully. Protect the legs and feet of tables, chairs, shelving and occasional furniture with soft rubber pads.
Do not use	Chlorine Bleach Ammonia Soaps or detergents that are not pH neutral Metal brushes or scourers Abrasive products
Routine cleaning	Clean with water and a specific concentrated cleaner, diluted as a conventional detergent, using a mop or damp cloth. pH-neutral soaps may also be used.
Stains	For difficult or persistent soiling, use a specific professional cleaner undiluted: spray it on, leave it to act for a few moments and remove the excess with a damp cloth. Clean up any spill of water, coffee, wine or other liquids immediately. Do not leave the cleaning product in prolonged contact with the surface, so as not to damage the protective layer.
Maintenance	Periodically renew the protective layer with acrylic wax — which is not Limewax — as it adds hardness and preserves the original appearance of the surface. How often it is waxed depends on the use and on the conditions of the place.